



INSEAM BOREHOLES TO AND BEYOND 2000 M WITH A COMBINATION OF SLIDE AND ROTARY DRILLING

F Hungerford


Half Day Seminar,
Gas and Coal Outburst Committee,
June 2016









- Deflection of DHM used for steering
- A B
- Flip-flopping slide drilling
- In-hole friction causing surging, slower feed and eventual termination
- Increased bit diameter to 96mm, increased bend to 1.25 deg, Asahi 4/5 DHM














- Depth capacity increased to 1500m but variable
- Record in-seam depth of 1763m set at Newlands in 2001
- Rotary/slide limited in use U/G
 - Appin in 1986 dived into floor
 - Appin along block 1000m
 - China "slide one/rotate one"






Longhole Drilling Challenge



- Developing into a new longwall domain in the Bulli Seam with no access for lateral drainage drilling
- Staged drainage and development would suffer delays
- Longwall block 2000m long with access from the southern end
- 2000m had never been drilled before
- AMT DGS survey instrument upgraded but never assessed for depth limit – DDM-MECCA previously preferred
- Drill Rod capacity CHD preferred
- Water pump capacity
- Asahi PCD Bit and Accu-drill 4/5 DHM
- Alternate drilling method required












- High gas flows expected
- Standpipe extension attached to manage removal of DHM









Drilling method:

- 1.125 deg bend with 1mm thick wear pad (Equivalent to 1.23 deg)
- 96mm bit increased to 99mm after first hole
- Rotary drill whenever possible and borehole is controlled in-seam
- Limit rotational speed to 40-60 rpm
- Define seam profile with regular intersections in first borehole – gas content core as required
- Record:
 - Drilling mode
 - Feed pressure and hold-back pressure
 - Water idle and drilling pressure
 - Main pump pressure when rotary drilling
 - Intermediate "check-shot" survey
 - Assessment of rotational speed





Drilling Record



VLI DRILLING PTY LTD

MINE:	
درية	ctro
HOLE No: 0406	08170708
LOCATION: 30	07.1

RIG:	ULT 20
DRILLER(S):	Tim WOODSY
DATE:	1-12-15

MINE DECLINATION:	ton	11.1
ENTRY HDG ENTERED:		26.8
DESIRED HDG ENTERED:		18.8

	1
A MENBER OF THE TRUTHEN THE THE THE GROWN A	Petalle.


d	DHM-DDM	DRILLING	i LC)G				
18		SHEET No:	0	5	6	1	2	

	Der	oth (m)								_	`	/			000	mbo fuso
Rod N	From		Notes	Feed	Wate	r			St	irvey						
	From	То			ldle Drill	Flow		Comments		Depth	Direct	Dip	Orient	I no fer	T	T :-
700	11100	1.11.6	_	1600 4	40 540	190				Deptil	17.7	-	-	D/Track	L/R	U/D
50	11120	(161	2,2	1509400 4	40 520	190	BIACK		BUACIL	1158	-		126			
200	-	ļ.,		1651200 4	40 620	190	BUACU		BUTCH	0,03	-	-7.8	41	1150-6	50.4	-7:7
28	11161	1167	R, R	1000 4	201120	190	BLACK		2.2010	11111	11.5	-2.3	342			
				1600 4	20 620	190	00.00	MP. 1500P	BUACIL	1164	19.7	-2.4	274	1129.9	50.3	-7.9
391	1167	1173	RR	1600 4	20 625	190	BLACK	171. 13001			18.6	-2.2	233			
			,	1409300 4	20 560		Bonce		BIACU	1170	183	-1.7	75	1162-6	50.2	-8.2
393	1173	1179	R. R	1600 4	40 580	190	BUTEL		^		18.3	-2.0	135			
			,	1609 4	40 620		00.00	MP. 1500	BLACK	1776	17.3	-1-8	67	1168-6	50.1	-8.3
395	1179	1185	R, R	1200 4			BUAGE	1111 : 1500	8:0.1		17.4	-1.8				
			,		40 640		ograc		BLACK			-1.4		11745	50.0	-8-5
397	1185	1191	B. 3	11 463	40 520		BLACK		0 0 -	1100	17.6	-1.4	267			
			,	11500 4	40 560		barac	Mp. 400	BUAGE	1188	17.8-	0.9	130	11805	49.9	-8-6
399	1191	1197	2, 2	111 00/	LO 560		BLACK			1	11.4	-09	h5 !	5 (0)		
			,	10004004	0 540		BOTTUL	PHO 1193m	BLACK	1194	17-5	-0.7	42	11865	49.8	-8.7
401	1197	1203	2. 2	1600 4	60 540	190	BLACK				1831	0.4	92	- Y		
				160842 /1	40 540	190	BUTTUL		BLACK	1200	9.2	0.01	17	11925	49.7	8.3
403	1203	1209	3. R	11000 44	to 600	190	BLACK	4			9.7	0.5	127	*.* .		
			-	1600 40	to 580	190	BUTGL	1	BLACK	12019	19.9	10	61 1	198.5	49.8.	-8.8
405	1209	1215	R. R		10 560	-	BLACK				20·SI	-1.01	114		\$ 181 W	
				1600 41	0120	190	Buriac		BLACK	212/	10.0	0.7	25 1	2045	49.9 -	8.9
407	1215	1221	R. R	1000 41	0 670	190	B. De.			- 10	20.71-	2.01	159			
		7)	1009/100 4	0 540	190	BLACK	4	BUACC 1	218	21.9	0.6	148	1210-58	50.1 -	9.0
409	1221	1227	12, 11	1000	0 540		00		1	12	0.31	0.0 1	3<9	4		
	,)		10 580	190	BLACK	2410	BLACK 1	224	20.24	J-8/	340	216.5	50.3 -	9.0
				200 4	M1200	110		P++@ 1222m			20.3	fulf 3	303	1		
20000 06	22 05 005 1	re n											-		-	





- Regular roof intersections
- Borehole and future cut-through crossings indicated
- New world record






Borehole Depth Summary



Borehole	Date	Depth (m)	Slide to (m)	Lat Dev (m)	Terminated
EX03	15/06/2015	1779	1746	116 L	No signal
EX02	19/07/2015	1875	1851	58 L	Floor
DH01	28/07/2015	1971	1803	31 L	Floor
DH04	9/08/2015	2001	1821	129 L	Roof
DH05	31/08/2015	2007	1653	78 R	To design
DH08	23/09/2015	2151	1743	40 L	No rods
DH09	7/10/2015	2103	1761	83 L	No rods
DH10	27/10/2015	2007	1761	121 L	To design
DH11	17/11/2015	2016	1920	166 L	No rods
DH06	8/12/2015	2007	1923	145 R	No rods
DH07	22/12/2015	2013	1884	0 L/R	No rods










Final Borehole Layout










Drilling method:

- Modular Series 1000 with 104 kN thrust capacity used on first 8 holes
- Track-mounted Series 1000 with 140 kN thrust capacity used on last 3 holes
- Slide capacity increased to 1900m achieved by increase in thrust capacity
- Thrust capacity reached as "no more feed capacity" rather than "surging and stalling"
- Drillers initially had no control with rotary drilling beyond end of slide
- Drillers experimented with rotary drilling control techniques (varied feed and rotation speed – to 180 rpm) with good results



Lateral Deviation – first site









Lateral Deviation – second site




























Rotation Pressure








Water Pressure

















Lateral Response









Borehole Deviation over 3m intervals


















DISCUSSION/CONCLUSIONS



- Bulli seam drilling conditions were very good with no instability experienced
- Use of rotary drilling was not regimented
- More work required to assess "control" of the rotary drilling section
- New underground in-seam drilling records
 - Slide at 1923m
 - Combination rotary/slide to 2151m
- 2000m long longwall block covered by in-seam drainage boreholes from remote access
- Is the gas flow sufficient to provide adequate drainage on schedule?
 - Considering seam gas is CO₂ and gas flow is restricted by borehole length
- What will be the gas flows when the boreholes are intersected and what mining procedures are required?
- Borehole locations to be adjusted with each intersection